



08-31-00

A

UNITED STATES PATENT APPLICATION TRANSMITTAL FORM

Box: NEW PATENT APPLICATION
ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Docket No.: **YOR9-2000-0351**

"Express Mail" mailing label number: EL 590 399 786 US
Date of Deposit: August 30, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and addressed to the Asst. Commissioner for Patents, Washington, D.C. 20231.

Suzanne Bates
(Name of person mailing paper)

Suzanne Baty
(Signature of person)

Sir:

Transmitted herewith for filing is the patent application of
Inventors:

Richard H. Boivie

For:

METHOD AND APPARATUS FOR TRACING A DENIAL-OF-SERVICE ATTACK BACK TO ITS SOURCE

Enclosed are:

- ☒ Declaration and Power of Attorney and an Associate Power of Attorney;
- ☒ **15** pages of Specification, **4** pages of Claims and **1** page of Abstract;
- ☒ **2** sheets of drawings;
- ☒ An Assignment of the invention to: International Business Machines Corporation, Armonk NY U.S.A., with Assignment Recordation Form;
- ☐ Information Disclosure Statement (and Form PTO-1449 with copies of cited documents);

The Filing Fee is calculated below.

CLAIMS AS FILED

(1)	(2)	(3)	(4)	(5)
For	Number	Number	Rate	Basic Fee
	Filed	Extra		\$690.00

Total Claims	21 - 20 = 1	\$ 18.00	\$ 18.00
--------------	---------------------------	----------	-----------------

Independent Claims	3 - 3 = 0	\$ 78.00	\$ 0
--------------------	-----------	----------	------

Assignment Recordal Fee:	<u>\$ 40.00</u>
TOTAL FILING FEE	<u>\$748.00</u>

-X- A check in the amount of \$748.00 in payment of the filing fee is enclosed.

_____ Charge \$ _____ to Deposit Account No. 01-0467.

Fee Deficiency: The Commissioner is hereby authorized to charge any additional fees under 37 C.F.R. 1.16 and 1.17 which may be required for this communication or during the entire pendency of this patent application, or credit any overpayment, to Deposit Account No. 01-0467.

Address all future communications to:

Harry F. Smith, Esq.
OHLANDT, GREELEY, RUGGIERO & PERLE, L.L.P.
One Landmark Square
Suite 903
Stamford, CT. 06901

Direct phone calls to Harry F. Smith at (203) 327-4500

8/30/2000
Date of Signature

Harry F. Smith, Esq.
Attorney for Applicant(s)
Ohlandt, Greeley, Ruggiero & Perle
Registration No. 32,493
(203) 327-4500

EXPRESS MAIL NO.: EL 590 399 786 US

International Business Machines Corporation Docket No.:

YOR-2000-0351

Ohlandt, Greeley, Ruggiero & Perle, L.L.P. Docket No.:

5 909.0019 USU

Patent Application Papers of: Richard H. Boivie

METHOD AND APPARATUS FOR TRACING A DENIAL-OF-SERVICE ATTACK BACK TO ITS SOURCE

FIELD OF THE INVENTION:

10 This invention relates generally to data communications networks including, but not limited to, the Internet and World Wide Web (WWW), and more specifically relates to methods and apparatus for tracing malicious behavior back to its source or sources. The teachings of this invention are particularly useful with that type of malicious behavior known as a denial-of-service attack.

15 **BACKGROUND OF THE INVENTION:**

Recently there have been a number of so-called "denial-of-service" attacks on servers of various WWW sites, or simply "web" sites. These attacks overwhelm the server with maliciously-generated traffic whose only purpose is to temporarily shut down the server, and, hence, the web site. As can be appreciated, even a temporary suspension of service
20 in a high volume commercial web site can result in a significant loss of revenue to the operator of the web site.

When a denial-of-service attack occurs it is desirable be able to trace the attack back to the machine (or machines) where the attack originated. However, the attacker may attempt to obscure the identity of the source of the attack. A need thus exists to provide
25 a network with an ability to determine a source or sources of maliciously-generated traffic.

OBJECTS AND ADVANTAGES OF THE INVENTION:

It is a first object and advantage of this invention to provide an improved data communications network having an ability to determine a source of a denial-of-service attack.

- 5 It is a further object and advantage of this invention to provide a denial-of-service attack tracing method, program and unit that is capable of tracing an attack back through a plurality of routers to the source of the attack.

SUMMARY OF THE INVENTION

10 The foregoing and other problems are overcome and the objects and advantages are realized by methods and apparatus in accordance with embodiments of this invention.

A method is disclosed for determining an identity of a source of undesirable packets received from a data communications network. The method includes steps of (i) operating a traceback function to receive at least one and possibly two input parameters, (a) a network address (v) of a device receiving the undesirable packets and
15 (b) a network address (r) of a packet router that is coupled to the device immediately upstream of the device; (ii) determining a set of network routers that are neighbors (n) of r; and (iii) querying individual ones of packet routers in order to determine a packet router that is a largest source of packets addressed to v via r, and continuing to query packet routers up through a hierarchy of interconnected packet routers until an identity
20 of a source of the undesirable packets is discovered, or until further backtracing becomes impossible or impractical. The step of operating the traceback function may operate the traceback function on a plurality of selected paths, where a particular path is selected based at least on an amount of traffic (volume) flowing through the path to or towards v.

- 25 A backtracking or traceback unit and method is also disclosed for tracing a denial-of-service attack on a victim machine, such as a server, back to its source. The backtracking unit includes a data processor that is responsive to a traceback computer program stored on a computer-readable media for receiving a first input parameter of an IP address (v) of the victim machine and a second input parameter of an IP address (r) of a router that
30 is immediately upstream of the victim machine. The traceback computer program controls the operation of the data processor to determine a set of routers that are

neighbors (n) of r and, for each neighbor n of r, to determine if r is n's next-hop for traffic addressed to v, where node n's next-hop for traffic addressed to v is the IP address of the node that n will forward a packet to if the destination address in the packet is v. The traceback computer program further controls the operation of the data processor, for the case where r is not n's next-hop for traffic addressed to v, to skip over n and to query the next neighbor of r, while for the case where r is n's next-hop for traffic addressed to v, to determine an amount of traffic that n is forwarding to r that is addressed to v. After determining the identity of the neighbor n of r that is the principal source of packets flowing to r that are addressed to v, the data processor continues further upstream from the determined neighbor n of r that is the principal source of packets flowing to r that are addressed to v to continue to traceback through interconnected routers until a source of denial-of-service attack packets to v is determined.

In one embodiment the data processor operates to send at least one Simple Network Management Protocol (SNMP) query to r to obtain information from a MIB, such as an ip forwarding table MIB, that stores IP addresses of routers that are neighbors of r. The data processor also operates to send at least one SNMP query to an IP Forwarding Table MIB of router n. It should be realized that the teachings of this invention are not limited for use with SNMP messages, and that other types can be used, as those skilled in the art should realize.

The data processor, while determining an amount of traffic that n is forwarding to r that is addressed to v, operates under control of the traceback computer program to send, in one embodiment, a first SNMP message to a neighbor router n instructing router n to count the number of packets that it is sending to router r that are addressed to v, and further operates to send a second SNMP message to router n to query router n as to how many packets it has sent to router r addressed to v. In another embodiment, where a packet router is already counting packets that it forwards, a first message can be sent to request the packet count and a second message can be sent later to request the count again. By subtracting the first count from the second count one is enabled to determine how many packets were forwarded during a certain interval. In a further embodiment the router may maintain a count of how many packets were sent during some interval, such as one second. In this case the message sent to the packet router may simply request this number. In a further embodiment the packet router is instructed to install a host route to the victim that tracks the existing route, and then query the packet router to determine the number of packets that were forwarded using the more specific host route.

The backtracking unit may also take corrective action by, for example, establishing a black hole host route to v as close as is possible to the source of the denial-of-service attack packets, and/or by establishing a special host route to v using the same next hop as an existing route, where the special host route tracking changes in the existing route such that when a next hop for the existing route changes, the next hop for the host route changes similarly, and/or by establishing a rate-limit, for packets addressed to v, as close as is possible to the source of the denial-of-service attack packets.

BRIEF DESCRIPTION OF THE DRAWINGS

The above set forth and other features of the invention are made more apparent in the ensuing Detailed Description of the Invention when read in conjunction with the attached Drawings, wherein:

Fig. 1 is a simplified diagram of a data communications network and related components, including servers and routers;

Fig. 2 is a block diagram of a denial-of-service attack traceback unit in accordance with the teachings of this invention; and

Fig. 3 is a logic flow diagram depicting a method executed by the denial-of-service attack traceback unit of Fig. 2.

DETAILED DESCRIPTION OF THE INVENTION

It is first noted that in copending and commonly assigned U.S. Patent Application 09/_____, filed on even date herewith, entitled "Method for Protecting Web Servers Against Various Forms of Denial-of-Service Attacks", the inventor teaches several techniques for defending against an occurrence of a denial-of-service attack. The disclosure of this commonly assigned U.S. Patent Application is incorporated by reference herein in its entirety. It is further noted that the malicious traffic (e.g., denial-of-service attack) traceback teachings of this invention may be used in conjunction with the various techniques for protecting against such attacks disclosed in the commonly assigned Patent Application, as well as with other types of defensive mechanisms. For example, once a server or a firewall or a router determines that a denial-of-service attack is underway, and defensive mechanisms are deployed or are being deployed, the teachings of this invention can be used to traceback to the source of the denial-of-service

attack.

Fig. 1 is a simplified illustration of a data communications network 10, which may be coupled to the Internet 12. The network 10 may be referred to as an enterprise network. A server 14 is bidirectionally coupled to the network 10 and receives traffic therefrom, and outputs traffic thereto. The traffic is comprised of packets that conform, in the presently referred embodiment, to the well-known TCP/IP protocol. Also coupled to the server 14, via the Internet 12 and the data communications network 10, are a plurality of user terminals and computers, such as workstations and personal computers (PCs) 18, as well as other servers 20. Firewalls 22 and routers 24 are also typically present. The router 24 will typically have nearest neighbor routers 24A, 24B etc., and has knowledge of the identities of its nearest neighbor routers (as explained below in the discussion of MIBS). It is assumed that server 14 is a target of malicious traffic launched from one or more of the computers 18 and/or servers 20, i.e., that the server 14 is the target of a denial-of-service attack.

Before proceeding further with a description of the denial-of-service traceback method and apparatus of this invention, a number of definitions are first given for terms and phrases that have appeared and that will appear in the ensuing detailed description, or that are related to these teachings. These various terms and phrases are useful in gaining an understanding of the various types of denial-of-service attacks that a particular server 14 may be subjected to.

IP:

Internet Protocol.

TCP:

TCP is the Transmission Control Protocol. TCP is used to provide a "reliable" connection between two nodes in an internet. TCP uses sequence numbers, checksums, acknowledgments (or ACKs) and retransmissions of lost or garbled data to provide reliability. TCP is used by applications where it is important to deliver bytes correctly, such as mail, web browsing etc.

UDP:

UDP is the User Datagram Protocol. UDP does not provide sequence numbers, checksums, ACKs, retransmissions or reliability. It is used by those applications in which the "timeliness" of packet delivery is important, and the retransmission of lost or

garbled data is not important. IP telephony is an example in which the timeliness of packet delivery is important and the retransmission of lost or garbled packets is not useful.

TCP SYN:

- 5 TCP uses TCP SYN packets to initiate a TCP connection.

TCP ACK:

TCP uses ACK packets to acknowledge the successful receipt of (ungarbled) data.

A TCP connection is set up with a 3-way "handshake", as follows.

- 10 (a) The initiator sends a SYN packet that includes some "Synchronizing" information.
(b) The server responds with a SYN packet that includes some Synchronizing information of its own. The server's SYN packet also ACK's the Synchronizing information that was received from the initiator.
(c) The initiator ACK's the information in the server's SYN packet.

TCP FIN:

- 15 TCP uses TCP FIN packets to close a TCP connection.

SYN Bit On, ACK bit Off

The SYN Bit in the TCP header is On and the Ack Bit is Off in the first packet in the 3-way handshake, described above, that is used to initiate a new TCP connection.

TCP Connection/Watching SYNs and FINs

- 20 A TCP connection has two "ends", where each is defined by an IP address and a TCP port number. A TCP connection is established in a 3-way handshake as described above. A TCP connection is ended via a 3-way exchange of FIN (French for "end") packets. If one keeps track of the SYN and FIN exchanges one can determine if a TCP packet is part of a legitimate TCP connection, or if it is a packet sent from an attacker
25 that should be discarded.

Partially Established TCP connection:

A TCP connection that is not completely established, i.e., one which is waiting for the third packet (ACK) in the 3-way handshake.

Random Early Drop:

Random Early Drop is a defense against a TCP SYN attack. When a new TCP SYN arrives, the TCP implementation in a server 14 checks to determine if any free TCP control blocks are available. If so, it allocates one to the new connection. If not, it uses a TCP control block from a "Partially Established" TCP connection. Since "real" TCP
5 connections will not normally stay in the "partially established" state for very long, because the third packet in the 3-way handshake will normally arrive "shortly" after the sending of the second packet in the 3-way handshake, the re-use of the "partially established" TCP connection's control block will normally not impact legitimate traffic, but it will reclaim control blocks so that they can be used for legitimate TCP
10 connections.

denial-of-service attack:

A set of one or more packets that is sent to a web site or other site on the Internet for the purpose of "boggling down" or disabling the site.

ping attack:

15 An attack in which the attacker attempts to "bog down" a site by sending it a stream of "ping" packets. A ping is an icmp echo request packet (considered herein to be a non-TCP packet). A node is expected to respond to an icmp echo request with an icmp echo response. A ping is normally used to determine if a host is up and if the path to and back from the host is working. However, if an attacker sends large numbers of pings
20 very rapidly, the host can become bogged down and it may be difficult for the host to provide service to legitimate users.

smurf attack:

An attack in which the attacker sends "broadcast" ping packets to a number of machines with a forged source address such that the source address in the packet is that of the
25 "target" machine or server, i.e., the server that the attacker wants to disable. When a broadcast ping is received by the presumably large number of machines, they each respond to the ping by sending an echo reply to the address that was in the source address field in the broadcast ping packet. Since the source address is that of the target server, the target server becomes overwhelmed with large numbers of echo replies. The
30 target server discards these echo replies, but the load on the target server node and the load on the link connecting the target server node to the network is large, such that the load can bog down both the target server node and the link.

TCP SYN flood:

5 A TCP SYN flood attack operates as follows. The attacker sends a large number of TCP SYN's to the target server 14. The attacker typically uses fake source addresses in these packets so that the attacker cannot readily be traced. The attacker also typically uses a different source address in each packet to make it difficult for the target server 14 to know that it is the subject of a TCP SYN attack. Each time a SYN is received, the target server 14 responds with the second packet (SYN) in the 3-way handshake. It also allocates some "resources" (e.g., a TCP control block that is to be used to keep track of the TCP connection). If enough TCP SYN's arrive at the target server 14, a considerable amount of resources become allocated and thus unavailable for handling legitimate traffic, and these allocated resources are not freed for some time, as the target server 14 is expecting the third packet (the ACK from the initiator) in the 3-way handshake. However, in this case the third ACK packet never arrives, nor does the expected real TCP exchange of data. Since the third packet of the handshake is never received, the allocated resources remain allocated for some time, until the target server 14 eventually
10
15 frees them. If enough resources are allocated and remain allocated, the resources of the target server 14 become depleted, and the target server 14 is not able to respond to legitimate traffic.

UDP Flood:

20 An attack in which the attacker sends large numbers of UDP packets to the target server 14. A UDP flood is similar to a ping attack.

TCP ACK Flood:

25 An attack in which the attacker sends a flood of TCP packets in which the ACK flag is set. The ACK flag is normally set to acknowledge the reception of ungarbled data, but an attacker may set the ACK flag in a flood of packets in an attempt to make the packets appear to be part of an established TCP connection. In this way the attack packets are not filtered out by the firewall 22.

Firewall:

30 A firewall is the unit 22 that sits between the Internet 12 and the server 20 or between the Internet 12 and the enterprise network 10 to protect the server or the enterprise network 10 from various forms of Internet-borne attacks.

Rate limiting:

Rate limiting limits the rate (packets per unit of time) at which certain types of packets are admitted to a network 10 or to a server 14, 20. Rate limiting is used to defend

against certain forms of attack. For example, it's useful to admit ping packets so that one can trouble-shoot network problems. But it's not usually important that a server be able to respond to, for example, a million ping packets per second. So one may arrange, as described below, the network such that the firewall 22 or the router 24, for example, limit the rate at which ping packets or UDP packets arrive at the server 14 to protect the server from ping attacks, smurf attacks and UDP attacks. Note that one would not normally wish to rate limit TCP traffic at a web site, since this would slow down legitimate web traffic.

Wire-speed

The ability to process packets as fast as they arrive from the network.

Simple Network Management Protocol (SNMP)

The SNMP is used to manage IP networks. SNMP queries are sent to routers and other IP-based devices to obtain various kinds of management information. Management information is stored in the form of MIB's. The SNMP specification may be found at <http://www.rfc-editor.org/rfc/rfc1157.txt>. As will be made evident below, this invention may use SNMP queries, but is not limited for use with only SNMP queries and messages.

Management Information Base (MIB)

A MIB is a collection of related pieces of information. The router 24 of Fig. 1 is assumed to have a MIB for each of the routing protocols that it implements. Routing protocols are used to exchange routing information with other routers. OSPF, RIP and BGP are examples of routing protocols. A router that implements the OSPF routing protocol supports the OSPF MIB. Similarly, a router that implements the BGP protocol supports the BGP MIB. The route protocol MIBs on a given router *r* contain, among other things, the IP addresses of routers 24A, 24B, etc. that are neighbors of *r*. It is noted that the description of the MIB for the IP forwarding table may be found at <http://www.rfc-editor.org/rfc/rfc1354.txt>.

As is shown in Fig. 1, in a presently preferred embodiment of this invention a denial-of-service attack (DOS) traceback unit 15 is installed in the target server 14, or in a router 24,. The DOSA traceback unit 15 could also be installed in the (optional) firewall 22.

In the preferred embodiment the DOSA traceback unit 15 is embodied as computer program code, stored on a computer-readable media such as a disk or in a semiconductor

memory device 15B, that is executable by a computer or data processor 15A that forms a part of, by example, at least one of the server 14, the router 24, or the firewall 22. The processor 15A could be a dedicated processor for this purpose, or the processor 15A could be an already present data processor that runs in the server 14 or router 24 or firewall 22, and that is programmed to implement the DOSA functionality as described herein.

Referring to the logic flow diagram of Fig. 3, the DOSA traceback unit 15 of Figs. 1 and 2 operates as follows.

In a simplest case, at Step A a traceback program takes two input parameters, (a) the IP address of the victim machine, assumed for this example to be the target server 14, and (b) the IP address of the router that is immediately upstream of the target server 14. The first input parameter may be referred to as v, and the second input parameter may be referred to as r.

Step B determines the set of routers that are "neighbors" of r. The neighbors of a given router, r, can be determined by sending SNMP queries to r. As was explained above, SNMP is the Simple Network Management Protocol that is used to manage IP networks. SNMP queries are sent to routers and other IP-based devices to obtain various kinds of management information that is stored in the form of MIBs. The MIBs on a given router r include the IP addresses of routers that are neighbors of r. As such, the neighbors of the router, r, can be determined by sending SNMP queries to r.

It should be noted that the teachings of this invention are not limited for use with SNMP messages, and that other message types and protocols can be used as those skilled in the art should realize.

At Step C, for each neighbor n of r, determine if r is n's "next-hop" for traffic addressed to v, where node n's "next-hop" for traffic addressed to v is the IP address of the node that n will forward a packet to if the destination address in the packet is v. This determination can be made by sending SNMP queries to router n (in this case, to query router n's IP Forwarding Table MIB).

At Step D, if r is not n's next-hop for traffic addressed to v, then skip over n and go on to the next neighbor of r. On the other hand, if r is n's next-hop for traffic addressed to v, a determination is made as to how much traffic n is forwarding to r that is addressed

to v. This can be determined by sending another SNMP query to n. However, since n may not be keeping track of how many packets that it is sending to r that are addressed to v, several SNMP messages may be used to accomplish this step. The first SNMP message tells n to count the number of packets that it is sending r addressed to v. And
5 the second SNMP message, which is sent at some later time, queries n as to how many packets it has sent to r addressed to v. Step D is performed for each of the neighbors of r.

In another embodiment, where a packet router n is already counting packets that it forwards, a first message can be sent to request the packet count and a second message
10 can be sent later to request the count again. By subtracting the first count from the second count one is enabled to determine how many packets were forwarded during a certain interval. In a further embodiment the router may maintain a count of how many packets were sent during some interval, such as one second. In this case the message sent to the packet router may simply request this number. In a further embodiment the
15 packet router is instructed to install a host route to the victim that tracks the existing route, and then one may query the packet router to determine the number of packets that were forwarded using the more specific host route.

Once the method determines the identity of the neighbor of r that is the principal source of packets flowing to r that are addressed to v, the process is continued one node further
20 upstream. For example, if it is determined that node s is the neighbor of r that is forwarding most of the packets addressed to v, the method attempts to determine the identity of the neighbor of s that is the source of most of the packets addressed to v that are being sent to s.

This process is then continued back through the interconnected routers until the source
25 of the malicious traffic packets is determined (Step E), or until further backtracking becomes impossible. For example, the operator of network A may backtrack to a network A router that is closest to the source, while the ultimate source of the malicious traffic may be located further upstream in network B. In this case network A may not have the necessary access permissions and visibility in network B to continue
30 backtracking. Rate limiting can be useful in this case, where traffic addressed to v can be limited (including legitimate traffic) while network B attempts to backtrack to the ultimate source. When the actual source is found the offending machine can be disconnected, and/or other appropriate action can be taken.

An example of pseudocode for an embodiment of the traceback program executed by the DOSA unit 15 data processor 15A is as follows:

```

5      /*
      * traceback - trace a denial of service attack back to a source
      *
      * usage: traceback host router
      *       where host is the ip address of the machine under attack
      *       and router is the ip address of the router that is immediately
      *       upstream of the machine under attack
10     */
      main(argc, argv)
          int argc;
          char *argv[];
      {
15          h = argv[0];
          r = argv[1];
          do {
              print (r);
              r = upstream(h, r);
20          } while r!= NULL;
      }

      upstream(h, r)
          ip_address h;
          ip_address r;
25      {
          /*
          * initialize variables needed to determine the next
          * node upstream that the attack is coming from
          */
30          next_node = NULL;
          max_traffic = 0;
          /*
          * determine the routers that are "neighbors" of router r
          * by looking at the MIBs on r (e.g. the OSPF MIB, RIP MIB,
          * BGP MIB etc.)
35          */
          n = the number of routers that are neighbors of r;
          for (i = 0; i < n; i++){
              nbr = the ith neighbor of r;
40              /*
              * then for each neighbor, nbr, determine if nbr is
              * upstream of r for traffic headed for v. This is done by
              * sending snmp queries to nbr to determine if r is nbr's
              * next hop for traffic that is going to v. This information
              * is assumed to be available in the IP forwarding MIB.
45              */
              if (nbr is upstream of r for traffic going to v){
                  /*
                  * do another snmp query to determine how
                  * much traffic nbr is sending to v thru r.
                  * if insufficient information in existing MIBs.
                  * then add new MIB variable (e.g., traffic)
50              */

```

```

        traffic = the amount of traffic that nbr is currently sending
                   to v thru r
        /*
        * keep track of the upstream neighbor that is
        * the largest source of this traffic
        */
5       if (traffic > max_traffic){
            max_traffic = traffic;
            next_node = nbr;
10      }
    }
    /*
    * finally, return the upstream neighbor that is the principal source of traffic
    */
15    return (next_node);
}

```

A denial-of-services attack may actually be a coordinated attack from a large number of sources. To handle this case the traceback program may be designed in such a way that

it can trace multiple attacks upstream, along multiple paths, if the volume of traffic to the victim server 14 is above a certain threshold on those paths. This can be done by adding a simple recursive function to the pseudocode implementation shown above.

Once the method has identified the source machine, or the router closest to the source machine, additional actions or corrective measures can be taken. For example, and in

addition to notifying the proper authorities, a "black hole" host route to the victim machine 14 can be added on the router 24 closest to the source machine so that malicious packets addressed to the victim machine 14 are routed into a "black hole". Note that if one is to route packets addressed to the victim machine 14 into a black hole, it is preferable to accomplish this as close to the source, and as far from the victim, as

possible to minimize the impact on legitimate traffic. A "black hole" route, if added for a particular IP address, implies adding a route table entry that tells the router 24 that packets addressed to that address should be routed "into a black hole" or dropped. A purpose of the "black hole" route is to eliminate the "denial of service" attack packets that are being sent to the victim machine 14. As was stated, in order to minimize the

impact of legitimate traffic, it is desirable to establish the black hole route as close to the source of the attack packets as possible. Ideally, the black hole route should be established at the machine that is the source of the attack packets.

Another corrective measure involves regulating (i.e., slowing down or rate-limiting) the flow of traffic to the victim machine 14 on the router 24 closest to the source. As with

the previous corrective measure, if one is going to slow down the flow of traffic to the

victim machine 14, it is preferred to do this as close to the source and as far from the victim machine as is practical in order to minimize the impact on legitimate traffic

It should be noted that the router 24 that is closest to the source of the malicious traffic in a given ISP might still be a number of hops or a number of ISP's away from the ultimate source of the malicious traffic. As such, a given ISP may not be able to identify the ultimate source of the attack, but it can still limit the damage in a way that tends to minimize the impact on traffic from other sources.

It is within the scope of these teachings to add a special host route to the victim machine or target server 14 on the routers 24. This special host route preferably uses the same next hop as the existing route that covers the address of the target server 14, and it also tracks changes in the existing route so that when the next hop for the route changes, the next hop for the host route changes similarly. This special host route is useful in several ways. For example, it allows one to distinguish traffic to the target server 14 from other traffic that uses the same net route in tracing an attack back to its source. Second, the special host route can also be used to slow or rate-limit the flow of traffic to the target server 14 without impacting traffic to other destinations that are covered by the same net route. To implement the special host route on a router or to utilize rate limiting on the host route, as described above, one would presumably require appropriate access authorization to "control" the router. As such, these tools may be limited to the owner of a certain network. On the other hand, the tools do provide the owner of the network with the ability to get closer to the source of the attack and to limit the damage.

In general, the special host route would be setup with same next-hop as the existing route that covers, or includes, the address of the target machine. The host route is employed only for the target server or victim. The host route would preferably track changes that are made to the existing route so that traffic for the host would continue to follow an appropriate path when routes change. However, using a separate route for the host provides several opportunities. For example, when the router forwards packets it may increment a counter when it uses a particular route, enabling the count of packets sent to the victim to be maintained. If the host route were not separated, then one may possibly only be able to count packets going to the network that the victim is attached to, although in some cases this may be adequate since the attack packets may constitute the majority of the traffic going to v's network. Also, the use of the host route enables rate limiting to be used on the host route, and thus avoiding unnecessarily applying rate limiting to other hosts that are on the same network.

Note should be made that while the invention has generally discussed the use of two input parameters to the traceback function, i.e., (a) an IP address (v) of the victim machine and (b) an IP address (r) of a router that is immediately upstream of the victim machine, if the traceback program or function is executed on a router or firewall that is upstream of the victim, one may require only one input parameter, namely the IP address of v.

Thus, while the invention has been particularly shown and described with respect to preferred embodiments thereof, it will be understood by those skilled in the art that changes in form and details may be made therein without departing from the scope and spirit of the invention.

CLAIMS

What is claimed is:

1. A method for tracing a denial-of-service attack on a victim machine back towards its source, comprising steps of:

operating a traceback program on at least one path to receive two input parameters, (a) an IP address (v) of the victim machine and (b) an IP address (r) of a router that is immediately upstream of the victim machine;

determining a set of routers that are neighbors (n) of r;

for each neighbor n of r, determining if r is n's next-hop for traffic addressed to v, or to a network that v is on, where node n's next-hop for traffic addressed to v is the IP address of the node that n will forward a packet to if the destination address in the packet is v;

if r is not n's next-hop for traffic addressed to v, skip over n and query the next neighbor of r, while if r is n's next-hop for traffic addressed to v, determining an amount of traffic that n is forwarding to r that is addressed to v; and

after determining the identity of the neighbor n of r that is the principal source of packets flowing to r that are addressed to v, continuing one node further upstream from the determined neighbor n of r that is the principal source of packets flowing to r that are addressed to v, and continuing to traceback through interconnected routers until a source of denial-of-service attack packets to v is determined or until further traceback is not possible.

2. A method as in claim 1, wherein the step of determining the set of neighbors comprises a step of sending at least one query to r to obtain information from a MIB that stores IP addresses of routers that are neighbors of r.

3. A method as in claim 1, wherein the step of determining if r is n's next-hop for traffic addressed to v comprises a step of sending at least one query to router n.

4. A method as in claim 3, wherein the step of sending at least one query queries

an IP Forwarding Table MIB of router n.

5. A method as in claim 1, wherein the step of determining an amount of traffic comprises a step of sending at least one message to a neighbor router n for determining a count of packets that router n is sending to router r that are addressed to v or to a network on which v resides.

6. A method as in claim 1, and further comprising a step of establishing a black hole host route to v as close as is possible to the source of the denial-of-service attack packets.

7. A method as in claim 1, and further comprising a step of establishing a special host route to v using the same next hop as an existing route, the special host route tracking changes in the existing route such that when a next hop for the existing route changes, the next hop for the host route changes similarly.

8. A method as in claim 1, and further comprising a step of establishing a rate-limit for packets addressed to v as close as is possible to the source of the denial-of-service attack packets.

9. A backtracking unit for tracing a denial-of-service attack on a victim machine back towards its source or sources, comprising a data processor responsive to a traceback computer program stored on a computer-readable media for receiving a first input parameter of an IP address (v) of the victim machine and a second input parameter of an IP address (r) of a router that is immediately upstream of the victim machine, said traceback computer program controlling operation of said data processor to determine a set of routers that are neighbors (n) of r and, for each neighbor n of r, to determine if r is n's next-hop for traffic addressed to v, where node n's next-hop for traffic addressed to v is the IP address of the node that n will forward a packet to if the destination address in the packet is v, said traceback computer program further controlling operation of said data processor for the case where r is not n's next-hop for traffic addressed to v, to skip over n and to query the next neighbor of r, while for the case where r is n's next-hop for traffic addressed to v, to determine an amount of traffic that n is forwarding to r that is addressed to v, and after determining the identity of the neighbor n of r that is the principal source of packets flowing to r that are addressed to v or to a network to which v is connected, for continuing further upstream from the determined neighbor n of r that is the principal source of packets flowing to r that are addressed to v to continue to

[illegible][illegible][illegible][illegible][illegible]

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

[illegible][illegible][illegible][illegible]

(r) that is coupled to the device immediately upstream of the device; and

querying individual ones of packet routers in order to determine a packet router that is a largest source of packets addressed to v via r, or to a network to which v is connected, and continuing to query packet routers up through a hierarchy of interconnected packet routers until an identity of a source of the undesirable packets is discovered or until further backtracking is not possible.

17. A method as in claim 16, wherein the steps of determining and querying each comprise a step of sending queries to the data communications network.

18. A method as in claim 16, wherein the step of querying comprises steps of:

sending a first network message to a packet router for instructing the packet router to determine a number of packets that it is sending addressed to v; and

sending a second network message to the packet router to query the packet router for the determined number.

19. A method as in claim 16, wherein the step of querying comprises a step of sending at least one message to a packet router for determining a number of packets being forwarded to or towards v.

20. A method as in claim 16, and further comprising a step of establishing at least one of a black hole host route to v as close as is possible to the source of the undesirable packets, establishing a special host route to v using the same next hop as an existing route, the special host route tracking changes in the existing route such that when a next hop for the existing route changes, the next hop for the host route changes similarly, and establishing a rate-limit for packets addressed to v as close as is possible to the source of the denial-of-service attack packets.

21. A method as in claim 16, wherein the step of operating the traceback function operates the traceback function on a plurality of selected paths, wherein a particular path is selected based at least on an amount of traffic flowing through the path.

METHOD AND APPARATUS FOR TRACING A DENIAL-OF-SERVICE ATTACK BACK TO ITS SOURCE

ABSTRACT OF THE DISCLOSURE

A backtracking method, program and unit for tracing a denial-of-service attack on a victim machine, such as a server, back towards its source. The backtracking unit includes a data processor that is responsive to a traceback computer program stored on a computer-readable media for receiving a first input parameter of an IP address (v) of the victim machine and a second input parameter of an IP address (r) of a router that is immediately upstream of the victim machine. The traceback computer program controls the operation of the data processor to determine a set of routers that are neighbors (n) of r and, for each neighbor n of r, to determine if r is n's next-hop for traffic addressed to v, where node n's next-hop for traffic addressed to v is the IP address of the node that n will forward a packet if the destination address in the packet is v. The traceback computer program further controls the operation of the data processor, for the case where r is not n's next-hop for traffic addressed to v, to skip over n and to query the next neighbor of r, while for the case where r is n's next-hop for traffic addressed to v, to determine an amount of traffic that n is forwarding to r that is addressed to v or to a network to which v is connected. After determining the identity of the neighbor n of r that is the principal source of packets flowing to r that are addressed to v, the data processor continues further upstream from the determined neighbor n of r that is the principal source of packets flowing to r that are addressed to v to continue to traceback through interconnected routers until a source of denial-of-service attack packets to v is determined. The data processor operates to send at least one query to r, such as a Simple Network Management Protocol (SNMP) query, to obtain information from a MIB that stores IP addresses of routers that are neighbors of r. The data processor also operates to send at least one query to an IP Forwarding Table MIB of router n. The data processor, while determining an amount of traffic that n is forwarding to r that is addressed to v, operates under control of the traceback computer program to send a first message to a neighbor router n instructing router n to count the number of packets that it is sending to router r that are addressed to v, and further operates to send a second message to router n to query router n as to how many packets it has sent to router r addressed to v.




Fig. 3

[illegible]

Docket No. YOR9-2000-0351

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND APPARATUS FOR TRACING A DENIAL-OF-SERVICE ATTACK BACK TO ITS SOURCE

the specification of which

(check one) **x** is attached hereto.

_____ was filed on _____ as Application Serial No. _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventor's certificate(s) listed below and have also identified below any foreign application(s) for patent or inventor's certificate(s) having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

(Number)	(Country)	(Day/Mon/Year Filed)	Yes	No
----------	-----------	----------------------	-----	----

I hereby claim the benefit under Title 35, United States Code, 119(e) and 120 of any United States application(s) listed below

and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Prov. Appl. No.)	(Filing Date)	(Status) (patent, pend., abandon.)
-------------------	---------------	---------------------------------------

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, as follows:

NAMES

Manny W. Schechter
Terry J. Ilardi
Christopher A. Hughes
Edward A. Pennington
John E. Hoel
Joseph C. Redmond, Jr.
Paul J. Otterstedt
Douglas W. Cameron
Wayne L. Ellenbogen
Stephen C. Kaufman
Daniel P. Morris
Louis J. Percello
Robert M. Trepp
David M. Shofi
Louis P. Herzberg

REGISTRATION NUMBERS

Reg. No. 31,722
Reg. No. 29,936
Reg. No. 26,914
Reg. No. 32,588
Reg. No. 26,279
Reg. No. 18,753
Reg. No. 37,411
Reg. No. 31,596
Reg. No. 43,602
Reg. No. 29,551
Reg. No. 32,053
Reg. No. 33,206
Reg. No. 25,933
Reg. No. 39,835
Reg. No. 41,500

SEND CORRESPONDENCE TO:

Harry F. Smith, Esq.
OHLANDT, GREELEY, RUGGIERO & PERLE, L.L.P.
One Landmark Square
Suite 903
Stamford, CT. 06901

DIRECT TELEPHONE CALLS TO:

Harry F. Smith, Esq.
Telephone: (203) 327-4500
Facsimile: (203) 327-6401

THE JOURNAL OF THE ROYAL ANTHROPOLOGICAL INSTITUTE

Inventor's
Signature Richard H Bowie Date 8/29/2000

Express Mail No.: EL 590 399 812 US

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:

INVENTOR: Richard H. Boivie

SERIAL NO.: 09/

ART UNIT:

FILED: Herewith

EXAMINER:

TITLE: METHOD FOR PROTECTING WEB SERVERS AGAINST
VARIOUS FORMS OF DENIAL-OF-SERVICE ATTACKS

ATTORNEY DOCKET NO.: YOR9-2000-0351

Hon. Commissioner of Patents and Trademarks
Washington, D.C. 20231

APPOINTMENT OF ASSOCIATE ATTORNEY

Dear Sir:

The undersigned attorney, who has been appointed as an Attorney of Record in the Declaration and Power of Attorney for the above-identified patent application, hereby appoints:

Harry F. Smith, Esq.

Reg. No.: 32,493

OHLANDT, GREELEY, RUGGIERO & PERLE, L.L.P.

One Landmark Square

Suite 903

Stamford, CT. 06901

as his Associate Attorney to prosecute said application and to transact all business in the United States Patent and Trademark Office connected therewith.

Please direct all official communications and telephone calls to:

Harry F. Smith, Esq.

OHLANDT, GREELEY, RUGGIERO & PERLE, L.L.P.

One Landmark Square

Suite 903

Stamford, CT. 06901

Telephone: (203) 327-4500

Facsimile: (203) 327-6401

Respectfully submitted,

8/30/00
Date

X Lauren Bruzzone
Lauren Bruzzone, Esq.

Reg. No.: 35,082

IBM Corporation

IP Law Department

Yorktown Heights, New York 10598

(914) 945-3247